

# HYUNDAI GRAVEMASKINER MED HJUL

## R130W -> R170W-7 (2004-2007)



**MOTOR** Mitsubishi S6S-DT  
Kapacitet: 16,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Dieselfleet CD+ 15W-40**

*Kontroller alle 10 timer, skift alle 500 timer*

**DIFFERENTIALE BAG**  
Kapacitet: 10 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 250 timer, skift alle 1000 timer*

**DIFFERENTIALE FOR**  
Kapacitet: 8,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 250 timer, skift alle 1000 timer*

**GEAR**  
Kapacitet: 3,2 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Kontroller alle 50 timer, skift alle 1000 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3

**Synfleet SHPD 10W-40**

*Kontroller alle 50 timer, skift alle 1000 timer*

# HYUNDAI GRAVEMASKINER MED HJUL

## R130W -> R170W-7 (2004-2007)



### NAVREDUKTIONER BAG

Kapacitet: 2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 250 timer, skift alle 1000 timer*

### NAVREDUKTIONER FOR

Kapacitet: 2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 250 timer, skift alle 1000 timer*

### HYDRAULISK SYSTEM

Kapacitet: 160 liter (Hydrauliktank), Kapacitet: 270 liter (System)

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Perlus H 68**

*Kontroller alle 10 timer, skift alle 2000 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Perlus H 46**

PRODUKTANBEFALING 2

**Perlus H 32**

*Kontroller alle 10 timer, skift alle 2000 timer*

# HYUNDAI GRAVEMASKINER MED HJUL

## R130W -> R170W-7 (2004-2007)



### SMØREPUNKTER/NIPLER

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 50 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                         |  |  |
|-------------------------|--|--|
| PRODUKTANBEFALING 1     |  |  |
| <b>Gear Grease EP 1</b> |  |  |

Skift alle 50 timer

### KØLESYSTEM

Kapacitet: 30 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                               |                     |  |
|-------------------------------|---------------------|--|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |  |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |  |

Kontroller alle 10 timer, skift alle 2000 timer

### DREJEGEAR

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Kontroller alle 50 timer, skift alle 1000 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                         |  |  |
|-------------------------|--|--|
| PRODUKTANBEFALING 1     |  |  |
| <b>Gear Grease EP 1</b> |  |  |

Kontroller alle 50 timer, skift alle 1000 timer

### SVINGREDUKTIONSGEARKASSE

Kapacitet: 5 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                |                                     |  |
|--------------------------------|-------------------------------------|--|
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2                 |  |
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 50 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

# HYUNDAI GRAVEMASKINER MED HJUL

## R130W -> R170W-7 (2004-2007)



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*