

HYUNDAI GRAVEMASKINER MED LARVEBÅND R110 -> R220LC-7H HYUNDAI D6BT-C



MOTOR Hyundai D6BT-C
Kapacitet: 16 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 180 liter (Hydrauliktank), Kapacitet: 290 liter (System)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

Skift alle 50 timer

HYUNDAI GRAVEMASKINER MED LARVEBÅND R110 -> R220LC-7H HYUNDAI D6BT-C

**KØLESYSTEM**

Kapacitet: 35 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 2000 timer***DREJEGEAR**

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1**SPORDREV GEARKASSER**

Kapacitet: 5,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 1000 timer***SVINGREDUKTIONSGEARKASSE**

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 50 timer, skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.