

HYUNDAI GRAVEMASKINER MED LARVEBÅND R110 -> R290LC-3 CUMMINS 6CT8.3-C (1994-2002)



MOTOR Cummins 6CT8.3
Kapacitet: 22,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

HYDRAULISK SYSTEM

Kapacitet: 380 liter (Hydrauliksystem inkl. tank), Kapacitet: 270 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 2000 timer/ 12 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

Skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

KØLESYSTEM

Kapacitet: 35 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

HYUNDAI GRAVEMASKINER MED LARVEBÅND R110 -> R290LC-3 CUMMINS 6CT8.3-C (1994-2002)



SPORDREV GEARKASSER

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer/ 6 måneder

SVINGREDUKTIONSGEARKASSE

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer/ 6 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.