

HYUNDAI GRAVEMASKINER MED LARVEBÅND R110 -> R480LC-9A LONG REACH CUMMINS QSX11.9 / TIER 4(2012)



MOTOR: Cummins QSX11.9
Kapacitet: 41,6 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof < 0,15 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof < 0,15 %	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Kontroller alle 10 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 262 liter (Hydrauliktank), Kapacitet: 380 liter (System)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Grease EP 1		

Skift alle 50 timer

HYUNDAI GRAVEMASKINER MED LARVEBÅND R110 -> R480LC-9A LONG REACH CUMMINS QSX11.9 / TIER 4(2012)

**KØLESYSTEM**

Kapacitet: 70 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 2000 timer***SPORDREV GEARKASSER**

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 1000 timer***SVINGREDUKTIONSGEARKASSE**

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 50 timer, skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.