

HYUNDAI GUMMIHJULSLÆSSERE HL HL730-3 DEUTZ BF4M-1012EC (1999-2005)



MOTOR Deutz BF4M-1012E
Kapacitet: 12,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

GEAR POWERSHIFT ZF 4WG310 4/3
Kapacitet: 20 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Almirol

Skift alle 1000 timer/ 6 måneder

SELVSPÆRRENDE DIFFERENTIALE BAG
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer/ 6 måneder

SELVSPÆRRENDE DIFFERENTIALE FOR
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer/ 6 måneder

HYUNDAI GUMMIHJULSLÆSSERE HL HL730-3 DEUTZ BF4M-1012EC (1999-2005)



HYDRAULISK SYSTEM

Kapacitet: 60 liter (Hydrauliktank), Kapacitet: 87 liter (System)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 68		

Skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	

Skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Grease EP 1		

KØLESYSTEM

Kapacitet: 35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.