

HYUNDAI GUMMIHJULSLÆSSERE HL HL730-9S CUMMINS QSB4.5 (2012 OG EFTER)



MOTOR Cummins QSB4.5
Kapacitet: 11 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth MSP 10W-40

PRODUKTANBEFALING 2
Agridiesel MSP 15W-40

PRODUKTANBEFALING 3
Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 500 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2
Armado Synth LSP Ultra 10W-40

PRODUKTANBEFALING 3
Armado Synth MSP 5W-40

Kontroller alle 10 timer, skift alle 500 timer

DIFFERENTIALE BAG

Kapacitet: 17,7 liter (+ navreduktioner)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer

DIFFERENTIALE FOR

Kapacitet: 17,7 liter (+ navreduktioner)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer

GEAR POWERSHIFT ZF 4WG130 4/3

Kapacitet: 20 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 1000 timer

HYUNDAI GUMMIHJULSLÆSSERE HL HL730-9S CUMMINS QSB4.5 (2012 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 92 liter (Hydrauliktank), Kapacitet: 134,5 liter (System)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 1		

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 30 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.