

HYUNDAI LÆSSERE, SKID-STEER HSL HSL500T KUBOTA V1305E



MOTOR Kubota V1305-E
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 10W-40

Skift alle 150 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 10W-40

Skift alle 50 timer

SLUTDREVTRANSMISSIONER
Kapacitet: 7 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 10W-40

Skift alle 1000 timer

HYDRAULISK SYSTEM
Kapacitet: 34 liter (Tank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 10W-40

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

HYUNDAI LÆSSERE, SKID-STEER HSL HSL500T KUBOTA V1305E



KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.