

HYUNDAI LÆSSERE, SKID-STEER HSL HSL850-7A KUBOTA V3307-T



MOTOR Kubota V3307-T
Kapacitet: 11,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

HYDRAULISK SYSTEM

Kapacitet: 64 liter (System), Kapacitet: 57 liter (Tank)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus H 68

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus H 32

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Grease EP 1

KØLESYSTEM

Kapacitet: 10,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

PRODUKTANBEFALING 2
Coolant -26

HYUNDAI LÆSSERE, SKID-STEER HSL HSL850-7A KUBOTA V3307-T



KÆDEKASSE

Kapacitet: 9,2 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.