

HYUNDAI MINIGRAVEMASKINER, MED LARVEBÅND R15 -> R80 R22-7 MITSUBISHI L3E (S/N HY2270001->) (2010 OG EFTER)



MOTOR L3E
Kapacitet: 3,5 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Synfleet SHPD 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

HYDRAULISK SYSTEM
Kapacitet: 33 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Grease EP 1

KØLESYSTEM
Kapacitet: 5,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

HYUNDAI MINIGRAVEMASKINER, MED LARVEBÅND R15 -> R80 R22-7 MITSUBISHI L3E (S/N HY2270001->) (2010 OG EFTER)



LARVEBÅNDSRULLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer

SPOR MELLEMHJUL

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer

SPORDREV GEARKASSER

Kapacitet: 0,33 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.