

IHI GRAVEMASKINER MED LARVEBÅND

45NX WG000001 ->



MOTOR Isuzu 4LE2
Kapacitet: 8,1 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 10 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 50 timer

IHI GRAVEMASKINER MED LARVEBÅND

45NX WG000001 ->



HYDRAULISK SYSTEM

Kapacitet: 84 liter, Kapacitet: 55 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Brug af afbryder	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Brug af afbryder	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 10 timer, skift alle 500 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SMØRINGSPUNKTER & NIPLER SVINGGEAR

Kapacitet: 3,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 1000 timer

IHI GRAVEMASKINER MED LARVEBÅND

45NX WG000001 ->



KØLESYSTEM

ANVEND

Forlænget

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF*Kontroller alle 10 timer, skift alle 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 6 måneder/ 250 timer*

KØREREDUKTIONSENHED

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30*Kontroller alle 500 timer, skift alle 1000 timer*

LARVEBÅNDSRULLER

Kapacitet: 0,06-0,08 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

MELLEMHJUL FRONT

Kapacitet: 0,07 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.