

IHI GRAVEMASKINER MED LARVEBÅND

9VX WB003011 -> (2007 OG EFTER)



MOTOR Yanmar 2TNV70-PIK
Kapacitet: 1,2-1,8 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 10 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 50 timer

IHI GRAVEMASKINER MED LARVEBÅND

9VX WB003011 -> (2007 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 14 liter, Kapacitet: 8,2 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Brug af afbryder	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Brug af afbryder	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 10 timer, skift alle 500 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

IHI GRAVEMASKINER MED LARVEBÅND

9VX WB003011 -> (2007 OG EFTER)



KØLESYSTEM

ANVEND		KLIMA
Forlænget		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 10 timer, skift alle 24 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 6 måneder/ 250 timer

KØREREDUKTIONSENHED

Kapacitet: 0,33 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 1000 timer

LARVEBÅNDSRULLER

Kapacitet: 0,05 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

MELLEMHJUL FRONT

Kapacitet: 0,02 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.