

INGERSOLL RAND KOMPAKTORER, SD-SERIE SD-105TF



MOTOR Cummins B3.9
Kapacitet: 9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

Skift alle 6 måneder/ 500 timer

DIFFERENTIALE
Kapacitet: 7,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer/ 12 måneder

NAV TIL DREJNINGSMOMENT TROMLEDREV
Kapacitet: 3,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer/ 12 måneder

PLANETGEAR
Kapacitet: 1,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer/ 12 måneder

HYDROSTATISK DREV
Kapacitet: 84 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

Skift alle 1000 timer/ 12 måneder

INGERSOLL RAND KOMPAKTORER, SD-SERIE SD-105TF



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 16,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 1000 timer/ 12 måneder

TROMLE EXCETRISK

Kapacitet: 7,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Abacot MEP HD 220		

Skift alle 1000 timer/ 12 måneder

TROMLEHOLDER

Kapacitet: 0,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Abacot MEP HD 220		

Skift alle 1000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.