

JCB GAFFELTRUCKS TIL HÅRDT TERRÆN

930 2WD JCB DIESELMAX TC-63 STAGE

IIIA/T3 (2008-2014)



MOTOR JCB TC-63
Kapacitet: 12-15 liter

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Armado Synth 5W-30

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

DIFFERENTIALE FOR

Kapacitet: 29,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 6 måneder/ 500 timer, skift alle 12 måneder/ 1000 timer

GEAR SynchroShuttle

Kapacitet: 17,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

JCB GAFFELTRUCKS TIL HÅRDT TERRÆN

930 2WD JCB DIESELMAX TC-63 STAGE

IIIA/T3 (2008-2014)

**HYDRAULISK SYSTEM**

Kapacitet: 64 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder***HYDRAULISK BREMSESYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 15*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease**KØLESYSTEM**

Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.