

JCB GRAVEMASKINER MED LARVEBÅND

8015 PERKINS 403C-11 (1997-2004)



MOTOR Perkins 403C-11
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	
Kroontrak MTH 10W-30	

Skift alle 100 timer

HYDRAULISK SYSTEM

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	
Perlus H 68	

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	
Perlus H 46	

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	
Perlus H 32	

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

JCB GRAVEMASKINER MED LARVEBÅND

8015 PERKINS 403C-11 (1997-2004)



DREJEDREV GEARKASSE

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Perlus H 68		

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 46		

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

DREJERING LEJER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

DREJERING TANDHJUL

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Compound OGL		

LARVEBÅNDSRULLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

JCB GRAVEMASKINER MED LARVEBÅND

8015 PERKINS 403C-11 (1997-2004)



SPOR MELLEMHJUL HJUL

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

SPORDREV GEARKASSER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.