

JCB GRAVEMASKINER MED LARVEBÅND

JS-260 LC STAGE IIIA/T3 (1773500- >1774499) (2008-2012)



MOTOR Isuzu 4HK1X
Kapacitet: 21,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 241 liter, Kapacitet: 120 liter (Hydrauliktank)

ANVEND

Fleksibel (max)

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 68

PRODUKTANBEFALING 3

Perlus AF 46

Kontroller alle 10 timer, skift alle 30 måneder/ 5000 timer

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32

Kontroller alle 10 timer, skift alle 30 måneder/ 5000 timer

ANVEND

Fleksibel væskeanalyse

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 68

PRODUKTANBEFALING 3

Perlus AF 46

Kontroller alle 3 måneder/ 500 timer

ANVEND

Fleksibel væskeanalyse

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32

Kontroller alle 3 måneder/ 500 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

Kontroller alle 50 timer

JCB GRAVEMASKINER MED LARVEBÅND JS-260 LC STAGE IIIA/T3 (1773500- >1774499) (2008-2012)



SMØREPUNKTER/NIPLER REKYLFIJEDERCYLINDER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

KØLESYSTEM

Kapacitet: 26,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder/ 4000 timer

KØREREDUKTIONSENHED

Kapacitet: 4,7 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

LARVEBÅNDSRULLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

SPOR MELLEMLJUL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

JCB GRAVEMASKINER MED LARVEBÅND JS-260 LC STAGE IIIA/T3 (1773500- >1774499) (2008-2012)



SVINGKRAANS LEJER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

Kontroller alle 1 måneder/ 250 timer

SVINGREDUKTIONSENHED

Kapacitet: 6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

SVINGRING TANDHJUL

Kapacitet: 17 kg

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

Kontroller alle 3 måneder/ 500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.