

JCB GRAVEMASKINER MED LARVEBÅND MICRO (M1148300 -> 1149552) (2004-2014)



MOTOR Perkins 403D-11
Kapacitet: 4,9 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 16 liter (Hydrauliktank), Kapacitet: 21 liter (System)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER ANDRE

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 10 timer

KØLESYSTEM

Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

KØREREDUKTIONSENHED

Kapacitet: 0,3 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 1 måneder/ 250 timer, skift alle 3 måneder/ 500 timer

JCB GRAVEMASKINER MED LARVEBÅND MICRO (M1148300 -> 1149552) (2004-2014)



SVINGKRANS LEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 50 timer

SVINGKRANS TANDHJUL

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.