

JCB GUMMIHJULSLÆSSERE 416B 1243000- >1317499 (1997-2001)



MOTOR Perkins 1000T
Kapacitet: 10,7 liter

ANVEND
Normal

KLIMA
Middelhavsgtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Synfleet SHPD 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

Kontroller alle 6 måneder/ 500 timer, skift alle 12 måneder/ 1000 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

Skift alle 100 timer

DIFFERENTIALE FOR
Kapacitet: 25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

Kontroller alle 6 måneder/ 500 timer, skift alle 12 måneder/ 1000 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

Skift alle 100 timer

JCB GUMMIHJULSLÆSSERE 416B 1243000- >1317499 (1997-2001)



GEAR

Kapacitet: 19 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 125 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 15

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

KØLESYSTEM

Kapacitet: 26 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 6 måneder/ 500 timer, skift alle 24 måneder/ 2000 timer

JCB GUMMIHJULSLÆSSERE 416B 1243000- >1317499 (1997-2001)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.