

JCB GUMMIHJULSLÆSSERE 456 ZX -> 539249 (2001-2006)



MOTOR Cummins 6CT8.3C
Kapacitet: 18,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 100 timer

DIFFERENTIALE BAG
Kapacitet: 51 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 100 timer, skift alle 1000 timer

DIFFERENTIALE FOR
Kapacitet: 51-69 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 100 timer, skift alle 1000 timer

GEAR Powershift
Kapacitet: 28 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 100 timer, skift alle 1000 timer

JCB GUMMIHJULSLÆSSERE 456 ZX -> 539249 (2001-2006)



HYDRAULISK SYSTEM

Kapacitet: 215 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

Skift alle 100 timer

KØLESYSTEM

Kapacitet: 38-40 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.