

JCB GUMMIHJULSLÆSSERE 467 ZX

QSM11 STAGE IIIA/T3 (2014 OG EFTER)



MOTOR QSM11
Kapacitet: 41 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

DIFFERENTIALE BAG ZF MT-L3105-II
Kapacitet: 42 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

Kontroller alle 6 måneder/ 500 timer, skift alle 18 måneder/ 1500 timer

DIFFERENTIALE FOR ZF MT-L3105-II
Kapacitet: 42 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

Kontroller alle 6 måneder/ 500 timer, skift alle 18 måneder/ 1500 timer

GEAR ZF 4WG260 4/3
Kapacitet: 42 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Skift alle 100 timer

JCB GUMMIHJULSLÆSSERE 467 ZX

QSM11 STAGE IIIA/T3 (2014 OG EFTER)



GEAR ZF 5WG260
Kapacitet: 42 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Skift alle 100 timer

HYDRAULISK SYSTEM
Kapacitet: 170 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 46

PRODUKTANBEFALING 2
Perlus H 46

Kontroller alle 10 timer, skift alle 24 måneder/ 4000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
HT Q9 High Grade Grease

PRODUKTANBEFALING 2
Labora Grease

SMØREPUNKTER/NIPLER CENTRALSMØRESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

JCB GUMMIHJULSLÆSSERE 467 ZX

QSM11 STAGE IIIA/T3 (2014 OG EFTER)



KØLESYSTEM

Kapacitet: 39 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 18 måneder/ 3000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.