

JCB TELESKOPISK HÅNDTAG (USA) LOADALL/AGRI 540-170 USA (93 KW) STAGE IIIB/T4I (2014 OG EFTER)



MOTOR JCB Ecomax T4i
Kapacitet: 15 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Armado Synth MSP 5W-40		

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 19 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

DIFFERENTIALE FOR
Kapacitet: 17,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

GEAR POWERSHIFT PS760
Kapacitet: 21 liter (Olieskiftskapacitet), Kapacitet: 23 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

JCB TELESKOPISK HÅNDTAG (USA) LOADALL/AGRI 540-170 USA (93 KW) STAGE IIIB/T4I (2014 OG EFTER)



NAVREDUKTIONER BAG

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

NAVREDUKTIONER FOR

Kapacitet: 1,9 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 180 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 15

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

JCB TELESKOPISK HÅNDTAG (USA) LOADALL/AGRI 540-170 USA (93 KW) STAGE IIIB/T4I (2014 OG EFTER)



KØLESYSTEM

Kapacitet: 28 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.