

JCB TELESKOPLÆSSER 510-56 STAGE IIIA (5CG) (2007-2013)



MOTOR JCB 444
Kapacitet: 12,5-15 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Armado Synth 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND
Krævende

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Armado Synth 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND
Bio-indhold i brændstof > 19 %

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND
Bio-indhold i brændstof > 19 %

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Armado Synth 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

JCB TELESKOPLÆSSER 510-56 STAGE IIIA (5CG) (2007-2013)



DIFFERENTIALE BAG

Kapacitet: 13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

DIFFERENTIALE FOR

Kapacitet: 18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

GEAR Powershift 4

Kapacitet: 19 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

NAVREDUKTIONER BAG

Kapacitet: 0,5 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

NAVREDUKTIONER FOR

Kapacitet: 0,5 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

JCB TELESKOPLÆSSER 510-56 STAGE IIIA (5CG) (2007-2013)



HYDRAULISK SYSTEM

Kapacitet: 128 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 15		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
HT Q9 High Grade Grease		

KØLESYSTEM

Kapacitet: 20 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.