

JCB TELESKOPLÆSSER 530 AA, 767001->



MOTOR Perkins 1004-4 (AA)
Kapacitet: 10 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SHPD 10W-40

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Multifleet SCD 10W

DIFFERENTIALE BAG
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agrifluid HT

DIFFERENTIALE FOR
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agrifluid HT

GEAR
Kapacitet: 21 liter, Kapacitet: 23 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF-F (Ford)

JCB TELESKOPLÆSSER 530 AA, 767001->



NAVREDUKTIONER BAG

Kapacitet: 2 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Agrifluid HT		

NAVREDUKTIONER FOR

Kapacitet: 2 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Agrifluid HT		

HYDRAULISK SYSTEM

Kapacitet: 112 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

HYDRAULISK BREMSESYSTEM

Kapacitet: 3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 15		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

JCB TELESKOPLÆSSER 530 AA, 767001->



KØLESYSTEM

Kapacitet: 23 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.