

JCB TELESKOPLÆSSER 536-60 (74 KW) STAGE II (2008-2013)



MOTOR JCB 444 (SB)
Kapacitet: 12-15 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND	KLIMA
Bio-indhold i brændstof > 19 %	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND	KLIMA
Bio-indhold i brændstof > 19 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

JCB TELESKOPLÆSSER 536-60 (74 KW) STAGE II (2008-2013)



DIFFERENTIALE BAG

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

DIFFERENTIALE FOR

Kapacitet: 17,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

GEAR Powershift

Kapacitet: 21 liter (Olieskiftskapacitet), Kapacitet: 23 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

JCB TELESKOPLÆSSER 536-60 (74 KW) STAGE II (2008-2013)



GEAR Synchro Shuttle SS700/750

Kapacitet: 11,5 liter (Olieskiftskapacitet), Kapacitet: 13,5 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

NAVREDUKTIONER BAG

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

NAVREDUKTIONER FOR

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 50 timer, skift alle 6 måneder/ 500 timer

JCB TELESKOPLÆSSER 536-60 (74 KW) STAGE II (2008-2013)



HYDRAULISK SYSTEM

Kapacitet: 125 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 15

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 22 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUKTANBEFALING

JCB TELESKOPLÆSSER 536-60 (74 KW) STAGE II (2008-2013)



information contained herein is subject to changes without notification.