

## JCB TELETRUCK TLT20G GM 3.0L:



**MOTOR** GM 3.0L  
Kapacitet: 8,2 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 2  
**Multifleet SHPD 10W-40**

**HYDRAULISK SYSTEM**  
Kapacitet: 55 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2  
**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3  
**Dieselfleet CD+ 15W-40**

**SMØREPUNKTER/NIPLER**

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Labora Grease**

PRODUKTANBEFALING 2  
**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3  
**MP Lithep Grease EP 2**

**KØLESYSTEM**  
Kapacitet: 11 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Coolant SP 15+**

PRODUKTANBEFALING 2  
**Coolant SP 12**

PRODUKTANBEFALING 3  
**Coolant -38 Organic NF**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*