

JCB VIBRATIONSRULLERE VM132PD CUMMINS B5.9 STAGE II/TIER 2



MOTOR Cummins B5.9-xxxC
Kapacitet: 14,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Dieselfleet MSP 15W-40

DIFFERENTIALE BAG JCB
Kapacitet: 22 liter (+ navreduktioner)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

DIFFERENTIALE BAG ZF
Kapacitet: 15 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

GEAR TROMLEDREV
Kapacitet: 1,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Abacot MEP Synth 220

PRODUKTANBEFALING 2

Abacot MEP 220

NAVREDUKTIONER BAG JCB
Kapacitet: 2,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

JCB VIBRATIONSRULLERE VM132PD CUMMINS B5.9 STAGE II/TIER 2



NAVREDUKTIONER BAG ZF

Kapacitet: 1,75 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

HYDRAULISK SYSTEM

Kapacitet: 55 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 68	Perlus AF 68	

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

KØLESYSTEM

Kapacitet: 19 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

VIBRATORSYSTEM

Kapacitet: 12 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Abacot MEP HD 150	Abacot MEP 150	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.