

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 40H (+6) FORD LGR-425



## MOTOR Ford LRG-425

Kapacitet: 4,3 liter, Filterkapacitet: 1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

### PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

### PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

### PRODUKTANBEFALING 2

**HDX 20W-50**

### PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

### PRODUKTANBEFALING 1

**Asyntho 5W-30**

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

## HYDRAULISK SYSTEM

Kapacitet: 265 liter (System), Kapacitet: 104 liter (Tank)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

### PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

### PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

### PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

Kontroller alle 10 timer, skift alle 1200 timer/ 24 måneder

## KØLESYSTEM

Kapacitet: 15,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

### PRODUKTANBEFALING 2

**Coolant -26**

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 40H (+6) FORD LGR-425



## BÆRENDE SVINGGEARS TANDHJUL

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

Skift alle 100 timer

## DRIVHJULNAV

Kapacitet: 1,2 liter (hvert nav)

|                                                    |                                                           |                  |
|----------------------------------------------------|-----------------------------------------------------------|------------------|
| ANVEND<br>Normal                                   |                                                           | KLIMA<br>Moderat |
| PRODUKTANBEFALING 1<br><b>Gearlube GL-5 80W-90</b> | PRODUKTANBEFALING 2<br><b>Unigear HS GL-3/GL-5 80W-90</b> |                  |

Kontroller alle 50 timer, skift alle 1200 timer/ 24 måneder

## HJULLEJER

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

Skift alle 500 timer

## SVINGLEJE

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

Skift alle 100 timer

## SVINGREDUKTIONSENHED

Kapacitet: 1,2 liter

|                                                    |                                                           |                  |
|----------------------------------------------------|-----------------------------------------------------------|------------------|
| ANVEND<br>Normal                                   |                                                           | KLIMA<br>Moderat |
| PRODUKTANBEFALING 1<br><b>Gearlube GL-5 80W-90</b> | PRODUKTANBEFALING 2<br><b>Unigear HS GL-3/GL-5 80W-90</b> |                  |

Kontroller alle 50 timer, skift alle 1200 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.