

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 40H (+6) FORD LSG-423



MOTOR Ford LSG-423

Kapacitet: 4,7 liter, Filterkapacitet: 0,9 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

HDX 20W-50

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

HYDRAULISK SYSTEM

Kapacitet: 265 liter (System), Kapacitet: 104 liter (Tank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1200 timer/ 24 måneder

KØLESYSTEM

Kapacitet: 15,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 40H (+6) FORD LSG-423



BÆRENDE SVINGGEARS TANDHJUL

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 100 timer

DRIVHJULNAV

Kapacitet: 1,2 liter (hvert nav)

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-5 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1200 timer/ 24 måneder

HJULLEJER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 500 timer

SVINGLEJE

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 100 timer

SVINGREDUKTIONSENHED

Kapacitet: 1,2 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-5 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1200 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.