

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 460SJ GM3.0



## MOTOR GM 3.0

Kapacitet: 4,25 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

*Skift alle 3 måneder/ 150 timer*

## NAVREDUKTIONER BAG

Kapacitet: 0,5 liter (hvert nav)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer*

## NAVREDUKTIONER FOR

Kapacitet: 0,5 liter (hvert nav)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer*

## HYDRAULISK SYSTEM

Kapacitet: 196,8 liter (System), Kapacitet: 152 liter (Tank)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

### PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

### PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

*Skift alle 1200 timer/ 24 måneder*

## SMØREPUNKTER/NIPLER

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Labora Grease**

### PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

### PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Skift alle 6 måneder/ 300 timer*

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 460SJ GM3.0



## KØLESYSTEM

|                                                      |                                           |                  |
|------------------------------------------------------|-------------------------------------------|------------------|
| ANVEND<br>Normal                                     |                                           | KLIMA<br>Moderat |
| PRODUKTANBEFALING 1<br><b>Coolant -38 Organic NF</b> | PRODUKTANBEFALING 2<br><b>Coolant -26</b> |                  |

## HJULLEJER

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

*Skift alle 1200 timer/ 24 måneder*

## SVINGLEJE

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

*Kontroller alle 3 måneder/ 150 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*