

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 600A GM 3.0L



MOTOR GM 3.0

Kapacitet: 4,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 3 måneder/ 150 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 3 måneder/ 150 timer

HYDRAULISK SYSTEM

Kapacitet: 140,8 liter (Hydrauliksystem inkl. tank), Kapacitet: 117,3 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Skift alle 1200 timer/ 24 måneder

KØLESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

DRIVHJULNAV

Kapacitet: 0,5 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 600A GM 3.0L



HJULLEJER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 1200 timer/ 24 måneder

SPINDEL/BÅSNING

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 3 måneder/ 150 timer

SVINGLEJE

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 3 måneder/ 150 timer

SVINGREDUKTIONSENHED

Kapacitet: 0,5 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-5 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.