

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 60HA DEUTZ F3L1011



## MOTOR Deutz F3L-1011

Kapacitet: 6 liter, Filterkapacitet: 0,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2    |  |
|------------------------|------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |  |

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3    |
|----------------------|----------------------|------------------------|
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |

## HYDRAULISK SYSTEM

Kapacitet: 227 liter (System), Kapacitet: 189 liter (Tank)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3  |
|---------------------------|---------------------|----------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus   | Kroontrak MTH 10W-30 |

Kontroller alle 10 timer, skift alle 2000 timer

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3   |
|---------------------|--------------------------|-----------------------|
| Labora Grease       | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Skift alle 250 timer

## BÆRENDE SVINGGEARS TANDHJUL

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3   |
|---------------------|--------------------------|-----------------------|
| Labora Grease       | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Skift alle 100 timer

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 60HA DEUTZ F3L1011

**DRIVHJULNAV**

Kapacitet: 0,5 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90***Kontroller alle 50 timer, skift alle 2000 timer***HJULLEJER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2***Skift alle 2000 timer***STYRESPINDEL**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2***Skift alle 100 timer***SVINGDREVS HJULNAV**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90***Kontroller alle 50 timer, skift alle 2000 timer***SVINGLEJE**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2***Skift alle 100 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.