

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 800A FORD LRG-425, S/NO. 83332 ->



ENGINE Ford LRG-425
Capacity: 4,25 liter

| USE | | CLIMATE |
|-----------------------------|-----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Kroontrak MTH 10W-30 | Asyntho 5W-30 |

Check every 10 hours, change every 3 months/ 150 hours

HUB REDUCTIONS FRONT
Capacity: 1,3 liter (each hub)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

HUB REDUCTIONS REAR
Capacity: 1,3 liter (each hub)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

HYDRAULIC SYSTEM
Capacity: 291 liter (Complete), Capacity: 151 liter (Hydraulic tank)

| USE | | CLIMATE |
|----------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 8 hours, change every 24 months/ 1200 hours

COOLING SYSTEM
Capacity: 15,1 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 800A FORD LRG-425, S/NO. 83332 ->



SWING BEARING

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 3 months/ 150 hours

WHEEL BEARINGS

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.