

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 800A GM3.0, S/NO. 83332 ->



MOTOR GM 3.0
Kapacitet: 4,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Asyntho 5W-30

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

NAVREDUKTIONER BAG
Kapacitet: 1,3 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

NAVREDUKTIONER FOR
Kapacitet: 1,3 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

HYDRAULISK SYSTEM
Kapacitet: 151 liter (Hydrauliktank), Kapacitet: 291 liter (Komplet)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

Kontroller alle 8 timer, skift alle 24 måneder/ 1200 timer

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 800A GM3.0, S/NO. 83332 ->



KØLESYSTEM

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

HJULLEJER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 1200 timer/ 24 måneder

SVINGLEJE

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 3 måneder/ 150 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.