

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 800AJ CATERPILLAR 3044C, S/NO. -> 83332



**MOTOR** Caterpillar 3044C/3,4  
Kapacitet: 10 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 3 måneder/ 150 timer

**NAVREDUKTIONER BAG**  
Kapacitet: 0,5 liter (hvert nav)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

**NAVREDUKTIONER FOR**  
Kapacitet: 0,5 liter (hvert nav)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

## HYDRAULISK SYSTEM

Kapacitet: 151 liter (Hydrauliktank), Kapacitet: 291 liter (Komplet)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
|----------------------------------|--------------------------|-----------------------------|
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 8 timer, skift alle 24 måneder/ 1200 timer

## KØLESYSTEM

Kapacitet: 5,5 liter (Motor kun)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |  |
|-------------------------------|---------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |  |

# JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 800AJ CATERPILLAR 3044C, S/NO. -> 83332



## HJULLEJER

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

Skift alle 1200 timer/ 24 måneder

## SVINGLEJE

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

Skift alle 3 måneder/ 150 timer

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*