

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR M400AJP KUBOTA OC60



MOTOR Kubota OC60
Kapacitet: 1,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Skift alle 3 måneder/ 150 timer

NAVREDUKTIONER BAG
Kapacitet: 0,5 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

NAVREDUKTIONER FOR
Kapacitet: 0,5 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 150 timer, skift alle 24 måneder/ 1200 timer

HYDRAULISK SYSTEM
Kapacitet: 19 liter (Tank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Skift alle 1200 timer/ 24 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 32	Perlus H 32	

Skift alle 1200 timer/ 24 måneder

JLG BOMLIFTE MED INDBYGGET FORBRÆNDINGSMOTOR M400AJP KUBOTA OC60



BÆRENDE SVINGGEARS TANDHJUL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Compound OGL EP 0/1		

HJULLEJER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 1200 timer/ 24 måneder

SVINGLEJE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 3 måneder/ 150 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.