



HYDRAULISK SYSTEM

Kapacitet: 18,2 liter (System), Kapacitet: 15 liter (Tank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Skift alle 1200 timer/ 24 måneder

BÆRENDE SVINGGEARS TANDHJUL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 3 måneder/ 150 timer

GEARLEJETS SVINGSKRUEGÆNGE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 1200 timer/ 24 måneder

HJULLEJER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 1200 timer/ 24 måneder

SPINDEL/BÅSNING BOMPINDE/-BÅSNINGER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

JLG ELEKTRISKE BOMLIFTE E N40E



SVINGLEJE

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 3 måneder/ 150 timer

TORQUE-HJULNAV

Kapacitet: 0,5 liter (hvert nav)

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-5 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Skift alle 3 måneder/ 150 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.