

# JLG SAKSELIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 500RTS DEUTZ F3L-1011



## MOTOR Deutz F3L-1011

Kapacitet: 6 liter, Filterkapacitet: 0,5 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                             |                               |
|-----------------------------|-----------------------------|-------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Kontroller alle 10 timer, skift alle 100 timer

## HYDRAULISK SYSTEM

Kapacitet: 167 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                  |                          |                             |
|----------------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 10 timer, skift alle 500 timer

## SMØREPUNKTER/NIPLER

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 100 timer

## HJULLEJER

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 2000 timer

## STYRESPINDEL

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 100 timer

# JLG SAKSELIFTE MED INDBYGGET FORBRÆNDINGSMOTOR 500RTS DEUTZ F3L-1011



## TORQUE-HJULNAV

Kapacitet: 0,5 liter (hvert nav)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 500 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*