

JLG SAKSELIFTE MED INDBYGGET FORBRÆNDINGSMOTOR CM33RT FORD VSG-411



MOTOR Ford VSG-411

Kapacitet: 3,3 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
HDX 20W-50	Multifleet SHPD 15W-40

Kontroller alle 10 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30

Kontroller alle 10 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	
Asyntho 5W-30	

Kontroller alle 10 timer

HYDRAULISK SYSTEM

Kapacitet: 91 liter (System), Kapacitet: 76 liter (Tank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

JLG SAKSELIFTE MED INDBYGGET FORBRÆNDINGSMOTOR CM33RT FORD VSG-411

**KØLESYSTEM**

Kapacitet: 13,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26**HJULLEJER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 2000 timer***STYRESPINDEL**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 50 timer***TORQUE-HJULNAV**

Kapacitet: 0,3 kg (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 500 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.