JLG TELEHANDLERS 4013 PERKINS 1004-40T



ENGINE Perkins 1004-40T Capacity: 8,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every	250 hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours change every	50 hours		

DIFFERENTIAL FRONT Capacity: 7,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change ever	y 1000 hours	
USE		CLIMATE
1.90.1		Maria de la contra

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
01 501	

Change every 50 hours

DIFFERENTIAL REAR

Capacity: 7,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Check every 250 hours, change every 100	S
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

JLG TELEHANDLERS 4013 PERKINS 1004-40T



TRANSFERBOX Capacity: 1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 1000 hours		
USE		CLIMATE
use Initial service		CLIMATE Moderate
Initial service		
Initial service PRODUCT RECOMMENDATION 1		

TRANSMISSION POWERSHIFT Dana Capacity: 12,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check every 8 hours, change every 1000 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Change every 50 hours			

HYDRAULIC SYSTEM Capacity: 160 liter (Hydraulic tank), Capacity: 220 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 10 hours, change every 1500 hours		

JLG TELEHANDLERS 4013 PERKINS 1004-40T



COOLING SYSTEM Capacity: 19,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change every 1500 hours			

WHEEL DRIVE HUB Capacity: 1,4 liter (each hub)		
USE	CL	IMATE
Normal	M	oderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 1000 hours		
USE	CL	IMATE
Initial service	M	oderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 50 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.