

JOHN DEERE CONSTRUCTION

GRAVEMASKINER MED LARVEBÅND 75D

TIER 3/STAGE IIIA (2008-2021)



MOTOR Isuzu 4LE2X
Kapacitet: 12,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 56 liter (Hydrauliktank), Kapacitet: 100 liter (System)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 10 timer, skift alle 5000 timer

ANVEND

Væskeanalyse

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 500 timer

KØLESYSTEM

Kapacitet: 10,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Væskeanalyse

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 500 timer

KØREREDUKTIONSENHED

Kapacitet: 1,2 liter

JOHN DEERE CONSTRUCTION

GRAVEMASKINER MED LARVEBÅND 75D

TIER 3/STAGE IIIA (2008-2021)



ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1081	SP Gear 5015	

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND	KLIMA
Væskeanalyse	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer

ANVEND	KLIMA
Væskeanalyse	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Kontroller alle 250 timer

ANVEND	KLIMA
Væskeanalyse	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1081	SP Gear 5015	

Kontroller alle 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.