

JOHNSTON FEJEMASKINER CX201 STAGE 3A (2013 OG EFTER)



MOTOR D754 TE3
Kapacitet: 6,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Armado Synth LSP Ultra 10W-40

Kontroller alle 10 timer, skift alle 300 timer/ 12 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Armado Synth LSP Ultra 10W-40

Skift alle 50 timer

GEAR HYDROSTATISK
Kapacitet: 12 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 50 timer

NAVREDUKTIONER BAG
Kapacitet: 0,6 liter (hvert)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer

HYDRAULISK SYSTEM
Kapacitet: 55 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 10 timer, skift alle 12 måneder/ 1500 timer

JOHNSTON FEJEMASKINER CX201 STAGE 3A (2013 OG EFTER)



HYDRAULISK BREMSESYSTEM

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Drauliquid-LV Super DOT 4	PRODUKTANBEFALING 2 Drauliquid-S DOT 4	

Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer

SMØREPUNKTER/NIPLER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 13 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

Kontroller alle 10 timer, skift alle 12 måneder/ 1500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.