

JUNGHEINRICH GAFFELTRUCK, DIESEL DFG DFG 16 AK AX-J PERKINS 404C-22 (2001-2003)



MOTOR Perkins 404C-22
Kapacitet: 8,9 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

DIFFERENTIALE
Kapacitet: 5 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

GEAR

Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

JUNGHEINRICH GAFFELTRUCK, DIESEL

DFG DFG 16 AK AX-J PERKINS 404C-22

(2001-2003)



HYDRAULISK SYSTEM

Kapacitet: 46 liter (Hydrauliktank), Kapacitet: 51 liter (System)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
HDX 20W-20	Perlus H 68

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
HDX 10W	Perlus H 46

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,45 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.