

# JUNGHEINRICH GAFFELTRUCKS, ELEKTRISKE EFG EFG 318 (2004-2008)



## HYDRAULISK SYSTEM

Kapacitet: 18 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

**Perlus H 68**

*Kontroller alle 1000 timer, skift alle 12 måneder/ 2000 timer*

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

PRODUKTANBEFALING 3

**Drauliquid DOT 3**

*Kontroller alle 6 måneder/ 1000 timer, skift alle 24 måneder/ 4000 timer*

## HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Skift alle 1000 timer/ 6 måneder*

## REDUKTIONSENHED

Kapacitet: 0,35 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**ATF Dexron II-D**

*Skift alle 1000 timer/ 6 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*