

# JUNGHEINRICH GAFFELTRUCKS, ELEKTRISKE EFG EFG 320 (2009 OG EFTER)



## HYDRAULISK SYSTEM

Kapacitet: 24 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Perlus H 68***Kontroller alle 1000 timer, skift alle 12 måneder/ 2000 timer*

| ANVEND                     | KLIMA   |
|----------------------------|---------|
| Biologisk nedbrydelig olie | Moderat |

PRODUKTANBEFALING 1

**Perlus Biosynth 46***Kontroller alle 1000 timer, skift alle 12 måneder/ 2000 timer*

## REDUKTIONSENHED

Kapacitet: 0,35 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**SP Gear 5015**

PRODUKTANBEFALING 3

**Gearlube GL-4 80W**

## STYRESYSTEM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Perlus H 68***Kontroller alle 1000 timer, skift alle 12 måneder/ 2000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.