

# JUNGHEINRICH GAFFELTRUCKS, ELEKTRISKE EFG EFG-D30 (2005 OG EFTER)

**GEAR**

Kapacitet: 3 liter

## ANVEND

Normal

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Gear Oil Alcat 50***Skift alle 1000 timer/ 12 måneder***HYDRAULISK SYSTEM**

Kapacitet: 34,5 liter

## ANVEND

Normal

## KLIMA

Tropisk

## PRODUKTANBEFALING 1

**Perlus H 68***Kontroller alle 1000 timer, skift alle 12 måneder/ 2000 timer*

## ANVEND

Biologisk nedbrydelig olie

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Perlus Biosynth 46***Kontroller alle 1000 timer, skift alle 12 måneder/ 2000 timer***SMØREPUNKTER/NIPLER**

## ANVEND

Normal

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Labora Grease**

## PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

## PRODUKTANBEFALING 3

**MP Lithep Grease EP 2****STYRESYSTEM**

Kapacitet: 0,5 liter

## ANVEND

Normal

## KLIMA

Tropisk

## PRODUKTANBEFALING 1

**Perlus H 68***Kontroller alle 12 måneder/ 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.