

JUNGHEINRICH GAFFELTRUCKS, LPG TFG

TFG 25 BS BH-J GM 3.0 L4 (2001-2003)



MOTOR GM 3.0 L4
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 53 liter (Hydrauliktank), Kapacitet: 58 liter (System)

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1

HDX 20W-20

PRODUKTANBEFALING 2

Perlus H 68

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

HDX 10W

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

JUNGHEINRICH GAFFELTRUCKS, LPG TFG

TFG 25 BS BH-J GM 3.0 L4 (2001-2003)



KØLESYSTEM

Kapacitet: 10,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.