

KOBELCO GRAVEMASKINER MED LARVEBÅND SK85MSR-3E ISUZU AP- 4LE2X (LF08-05501 ->) (2013 OG EFTER)



MOTOR Isuzu 4LE2X

Kapacitet: 10,3 liter (Servicepåfyldning), Kapacitet: 11 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Dieselfleet LSP Ultra 10W-30

HYDRAULISK SYSTEM

Kapacitet: 85 liter (Samlet systemvolumen), Kapacitet: 36 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32

KØLESYSTEM

Kapacitet: 13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

DREJEGEAR

Kapacitet: 4,9 kg

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KOBELCO GRAVEMASKINER MED LARVEBÅND SK85MSR-3E ISUZU AP- 4LE2X (LF08-05501 ->) (2013 OG EFTER)

**KØREREDUKTIONSENHED**

Kapacitet: 1,35 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90**SVINGREDUKTIONSENHED**

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90**SVINGREDUKTIONSENHED (HUS)**

Kapacitet: 0,15 kg

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.