

KOMATSU BULLDOZERE D D41-6

KOMATSU S6D102E-1



MOTOR Komatsu S6D102E-1

Kapacitet: 22,8 liter (Servicepåfyldning), Kapacitet: 26,8 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer/ 6 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 250 timer/ 6 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 6 måneder

GEAR 3/3

Kapacitet: 19 liter (Servicepåfyldning), Kapacitet: 22 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

KOMATSU BULLDOZERE D D41-6

KOMATSU S6D102E-1



SLUTDREV

Kapacitet: 13 liter (hvert)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 2000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 37 liter (Servicepåfyldning), Kapacitet: 73 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 2000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

KOMATSU BULLDOZERE D D41-6

KOMATSU S6D102E-1



DÆMPERHUS

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 2000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer

STYRING KOBLINGSHUS

Kapacitet: 74 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.