

KOMATSU BULLDOZERE D D41P-6

KOMATSU S6D102E (B30001->)



MOTOR Komatsu S6D102E-1

Kapacitet: 22,8 liter (Efterfyld), Kapacitet: 26,8 liter (Specificeret)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

GEAR

Kapacitet: 19 liter (Efterfyld), Kapacitet: 22 liter (Specificeret)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

SLUTDREV

Kapacitet: 13 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

HYDRAULISK SYSTEM

Kapacitet: 37 liter (Efterfyld), Kapacitet: 73 liter (Specificeret)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Skift alle 2000 timer

KOMATSU BULLDOZERE D D41P-6

KOMATSU S6D102E (B30001->)



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 30 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

DÆMPERHUS

Kapacitet: 1,1 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 2000 timer

STYRING KOBLINGSHUS

Kapacitet: 74 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

KOMATSU BULLDOZERE D D41P-6 KOMATSU S6D102E (B30001->)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.