

KOMATSU BULLDOZERE D D51PX-22

KOMATSU SAA6D107E-1



MOTOR Komatsu SAA6D107E-1

Kapacitet: 20 liter (Servicepåfyldning), Kapacitet: 23 liter (Tør efterfyld)

ANVEND

Normal (alternativ)

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 500 timer

ANVEND

Normal (foretrukne)

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Skift alle 12 måneder

ANVEND

Acceptabel

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer/ 6 måneder

ANVEND

Acceptabel

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 250 timer/ 6 måneder

SLUTDREV

Kapacitet: 4 liter (Servicepåfyldning), Kapacitet: 4,4 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 63 liter (Servicepåfyldning), Kapacitet: 123 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 2000 timer

KOMATSU BULLDOZERE D D51PX-22

KOMATSU SAA6D107E-1



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 35 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

RULLER

Kapacitet: 0,21 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.