

KOMATSU BULLDOZERE D D65E-8

KOMATSU 6D125 (45001->)



MOTOR Komatsu 6D125-1
Kapacitet: 30 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Synfleet SHPD 10W-40

Skift alle 250 timer/ 6 måneder

GEAR 3/3
Kapacitet: 52 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 30

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

MOMENTOMFORMER

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 30

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

KOMATSU BULLDOZERE D D65E-8

KOMATSU 6D125 (45001->)



SLUTDREV

Kapacitet: 31 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

HYDRAULISK SYSTEM

Kapacitet: 108 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 63 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

KOMATSU BULLDOZERE D D65E-8

KOMATSU 6D125 (45001->)



STYRING KOBLINGSHUS

Kapacitet: 70 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.